


AIR QUALITY SYSTEMS

EFFICIENT. EFFECTIVE. ENERGY SAVING.



ENERGY RECOVERY TRUE 3Å WHEEL

- Industry's highest recovery performance (AHRI Certified) and Recovery Efficiency Ratios (RER)
- Contaminant carry-over to less than .045%
- Anti-corrosion, anti-microbial anti-stick face coatings standard
- Extruded aluminum structural hub, spokes and rim system
- Available singly, in self-contained conditioning units, or as retrofits of existing wheels.



EP/EPD SERIES

- Provides ultimate level of performance in the transfer of energy
- Preconditions air for a conventional air handler or can perform as an independent, integrated system with a variety of heating and cooling options
- Indoor or outdoor installation
- Airflow capacities range from 2,000 to 70,000 CFM



ASCENDANT™ SERIES

- Conventional cooling and active desiccant hybrid system, optimized to deliver and control low dew point air, while minimizing regeneration energy input
- Can produce supply air humidity levels as low as 15 grains which can be delivered at any traditional supply air temperature
- High operating efficiency by utilizing conventional cooling and active desiccant dehumidification where they are most beneficial



FV SERIES

- High recovery efficiency with low pressure loss
- Designed for rooftop installation in but can easily be installed indoors and still provide a very quiet, continuous supply of fresh air
- Provides a healthy, comfortable indoor atmosphere in a cost efficient package
- Airflow capacities range from 600 to 10,000 CFM



PINNACLE® PRIMARY VENTILATION SYSTEM

- Manages 100% of a building's ventilation, humidity, and temperature, while simultaneously reducing energy loads
- Dual wheel dedicated outside air system designed to ventilate and deliver air direct to space
- Ideal primary air system utilized to decouple latent load of the building with the least amount of air
- Supports ductwork reduction and central plant energy reduction



ECONET

- Reliable and efficient Air Handling Unit Heat recovery, heating and cooling air are integrated to form a common circuit resulting in a more compact ventilation unit.
- Hydronic recovery pump package perfect for when True 3Å is not specified
- Recovers and uses energy that is unusable in traditional systems. Econet influences the entire energy chain to greatly reduce the energy requirement.



NEUTON™ CONTROLLED CHILLED BEAM PUMP MODULE

- State-of-the-art active condensation control effectively eliminates chilled beam condensation concerns.
- Reduces cost of a chilled beam installation by 30% or more by utilizing smaller pipe diameters, fittings, and fewer feet of pipe.
- Uses a fraction of the energy used by traditional pump systems.
- Virtually eliminates field control requirements at the zone level.




IQHC ACTIVE CHILLED BEAM

- Industry best capacity to energy consumption ratio
- Utilizes the lowest air and water pressure to enhance the overall energy benefit of chilled beams
- Universal duct and water connections for easy to installation
- Superior indoor air quality and energy efficiency.




LYRA II CASSETTE CHILLED BEAM

- Pi (Pressure Independent) Airflow control provides built-in flexibility
- Very low noise level combined with high flexibility and high cooling capacity
- Fastening brackets make for easy installation - only 1 person needed to install
- Diffuses air in 4 directions to provide high cooling capacity and high level of comfort



FLEXICOOL IQSA CHILLED BEAM

- Supply air beams are designed to manage high cooling effects
- Equipped with adjusting rails, comfort control, for the adjustment of air flow, cooling effect and flow pattern
- Capacity and flow directions easily adjustable
- Fastening brackets for quick and easy mounting - lift up - snap on



CHILLED BEAM WITH ACTUATED SLOTS (WEGA II / NOVA II / SILENCIA)

- Motorized Energy Control
- Flow pattern control to adapt to the frequent changes of the modern office
- Control and regulation equipment
- Heating function: water coil or electrical coils
- Lighting



QPVA PASSIVE CHILLED BEAM

- Provides convective cooling to a space without requiring air duct connection
- Designed for pendant or ceiling grid mount
- Lengths available include 4, 6, 8, 10, and 12 feet
- Utilized alone, or as a supplement to active chilled beams to reduce primary air required in a high sensible load room

EXCELLENCE IN SOLUTIONS

FläktGroup® SEMCO®

1800 East Pointe Drive / Columbia, Missouri USA / 573.443.1481 / sales.semco@flaktgroup.com

www.semcohv.com

© 1994-2019 SEMCO LLC. All rights reserved. SEMCO, Pinnacle, and the SEMCO logo are registered trademarks of SEMCO LLC. Any FläktGroup SEMCO purchase is subject to FläktGroup SEMCO standard terms and conditions. U.S. patented technology: 6,016,710 ; 6,199,388