

FLÄKTGROUP SEMCO FV-T RECOVERY MODULE

The FläktGroup® SEMCO® FV-T Recovery Module of outdoor air preconditioners has been specifically designed to be mounted to a Trane® Voyager® roof top unit to reduce the energy required to cool or heat the outdoor air by as much as 80 percent. When mounted together, the FläktGroup SEMCO FV-T Preconditioner also allows the Trane® Voyager® rooftop units to effectively and economically accommodate the three-to-four-fold increase in outdoor air quantities, which is recommended by the ASHRAE Standard 62, Ventilation for Acceptable Indoor Air Quality. This unique capability allows both new and existing buildings to benefit from healthy indoor environments.

The FläktGroup SEMCO FV-T Recovery Module is designed to improve humidity control when mounted to the Trane® Voyager® roof top equipment. Because the FläktGroup SEMCO FV-T unit preconditions the incoming air to the packaged equipment, the required refrigeration capacity can be reduced by as much as 70 percent. Thus, the cost of the FläktGroup SEMCO FV-T and its installation are typically offset by the reduced size of the Trane® Voyager® system.



KEY BENEFITS

- Economical compliance with ASHRAE Standard 62
- Reduced equipment first cost
- Improved cooling season humidity control
- Reduced humidification requirements during the heating season
- Improves the IAQ of existing facilities
- Improved comfort of occupied spaces
- Efficient and economical design
- Entire cabinet insulated to minimize energy loss



Use of the AHRI Certified™ mark indicates a manufacturer's participation in the certification program. For verification of certification for individual products, go to www.ahrinet.org.

SYSTEM DESIGN

- Compact, low profile design to conform to typical architectural requirements.
- Easy access to all internal components through a large hinged access door and removable roof panel.
- Outdoor air inlet and exhaust air outlet located at opposite ends of unit for maximum separation.

THE FUSION ENERGY RECOVERY WHEEL

- Industry's highest recovery performance (AHRI Certified) and Recovery Efficiency Ratios (RER)
- Easily removable wheel cassette module
- Proprietary zeolite composite coating that provides a superior contaminant carry-over performance to non-molecular sieve based wheels, such as those employing silica gel.

**fusion**



CABINET CONSTRUCTION

- Galvanized steel cabinet construction with enamel finish
- Floor built as a pan to ensure watertight design
- Supply and exhaust air fans
- Sized for quiet and efficient operation
- Mounted and balanced

ELECTRICAL PACKAGE WITH SINGLE POINT CONNECTION

- All motors wired to starters
- Accepts contact inputs for supply fan start/stop, wheel start/stop and unit start/stop
- Multiple options on input voltage to units

FILTER SECTIONS

- Filtration provided for both outdoor and return air hoods and dampers
- Airflow balancing dampers
- Provided with an intake hood with cleanable filter to limit rain and snow introduction.
- Exhaust air back draft damper



EXCELLENCE IN SOLUTIONS

FläktGroup® SEMCO™ delivers smart and energy efficient air distribution and air quality solutions to support every application area. We offer our customers innovative technologies, high quality and outstanding performance supported by more than fifty years of accumulated industry experience. The widest product range in the market, and strong market presence in 65 countries worldwide, guarantee that we are always by your side, ready to deliver Excellence in Solutions.

FläktGroup® SEMCO®

1800 East Pointe Drive / Columbia, Missouri USA / 573.443.1481 / sales.semco@flaktgroup.com

www.semcohvac.com

